Amendment and Response Serial No. 09/876,459 Page 2 of 10

Amendments to the Claims

- 1. (Currently amended): A chemical mixing system for preparing a and slurry having a desired insoluble solids content resulting from mixing at least first and second chemical components, the system and slurry comprising:
 - (a) a mix vessel containing a mix volume suitable for preparing the slurry from at least first and second chemical components, wherein at least one of the chemical components comprises insoluble solid particles, and wherein the mix volume is adapted to receive the chemical components from at least first and second component sources, respectively;
 - (b) a control system responsive to a measured conductivity value comprising a first conductivity sensor at a rosition effective to detect when a defined amount of one of the chemical components is added to the mix volume and a conductivity probe at a position effective to detect when a combined amount of the chemical components has the desired insoluble solids centent at a measured conductivity value, wherein the control system generates a control signal to control the addition of at least one of the chemical components to the mix volume when a slurry is prepared so that the addition of the at least one chemical component ean be is ceased when the slurry has a measured conductivity value corresponding equal to a reference conductivity and corresponding to a desired insoluble solids content;
 - (c) at least one valve disposed in the chemical mixing system at a position effective to regulate the amount of the at least one chemical component added to the mix volume, wherein the at least one control valve is actuated by the control signal generated by the control system and operative to vary the rate of addition of the at least one chemical component in response to the measured conductivity value of the slurry;
 - (d) a recirculation loop; and

Amendment and Response Serial No. 09/876,459 Page 3 of 10

- (e) a slurry having the an the desired insoluble solids content.
- 2. (cancelled)
- 3. (cancelled)
- 4.(Currently amended): The chemical mixing system and slurry of claim 1, wherein at least a portion of an internal surface of the mix volume vessel comprises a corrosion resistant material selected from the group consisting of an ultra high molecular weight polyethylene, a fluorinated polymer, and polypropylene.
- 5. (Currently amended) The chemical mixing system and slurry of claim 4, wherein the corrosion resistant material is a fluorinated polymer selected from the group consisting of a perfluoralkoxy polymer, polytetrafluoroethylene, fluorinated ethylene propylene, polyvinylidene fluoride, ethylene tetrafluoroethylene, and chlorotrifluoroethylene.
 - 6. (cancelled)
 - 7. (cancelled)
- 8. (Currently amended) The chemical mixing system and slurry of claim 1, wherein the first conductivity sensor is located at the mix vessel.
- 9. (Currently amended): The chemical mixing system and slurry of claim 1, wherein the first conductivity sensor is located in the recirculation loop.
- 10. (Currently amended): The chemical mixing system and slurry of claim 1, wherein the conductivity probe is located at the mix vessel.
- 11. (Currently amended): The chemical mixing system and slurry of claim 1, wherein the conductivity probe is located in the recirculation loop.

Amendment and Response Serial No. 09/876,459 Page 4 of 10

- 12. (Currently amended): The chemical mixing system and slurry of claim 1, further comprising a pump operationally coupled to the chemical mixing system to motivate the chemical components through the system.
- 13. (Currently amended): The chemical mixing system and slurry of claim 1, further comprising a discharge line for transmitting the slurry from the mix vessel to a point of use.

14-21. (cancelled)